



LoRaWAN® Operated Low Power Pressure Transmitter for Corrosive Liquid and Gas Media

- Compatible with all LoRaWAN® frequencies
- Wide range of industrial applications
- High accuracy
- Designed to meet outdoor applications
- Long-term durable performance in harsh environment
- Ultra-low power
- Suitable for corrosive liquids and gases



TECHNICAL SPECIFICATION

Sensor

• Range:	Selectable between 0~0.5 to 0~200	bar
• Accuracy: (combined linearity, hysteresis, repeatability)	±0.5 (typ.)	%Span
• Resolution:	±0.01	%Span
• Pressure Reference:	Vented Gauge, Sealed Gauge, Absolute	
• Temperature Coefficient of Zero:	≤±0.02	%FS/°C
• Temperature Coefficient of Span:	≤±0.02	%FS/°C
• Long Term Stability (1 year):	≤ 0.2	%Span
• Pressure Overload:	300 (range <1bar); 150 (higher range)	%FS
• Pressure Cycles (Zero to Full Scale):	10+	Million
• Compensated Temperature:	-10 ~ +70	°C

Power

• Power Supply:	Built-in Replaceable Lithium Battery, External Power (option)	
• Rated Voltage	3.6	V
• Battery Lifetime:	50,000+ readings and 10,000+ transmission (More than 10 years for most applications)	

Physical Specification

• Materials:	Body: Hastelloy or PVDF, Diaphragm: Hastelloy or Ceramic (Al ₂ O ₃), Enclosure: PVDF/POM, O-ring: FKM/ FFKM	
• Process Connection:	G1/2 Male (or others on request)	
• Weight:	550	g
• Protection Rate:	IP65 /IP67, UV Protected	-

Communication

• LoRaWAN® Version, Class:	1.0.2revB, Class A (Class C on request)
• LoRaWAN® Frequency Zone:	AS923, EU868, US902-928, AU915-928 (other zones available on request)
• LoRaWAN® Activation Type:	OTA (default), ABP
• Sampling Type:	Periodic (default), Event triggered
• Sampling Period:	Configurable via downlink (default 4 hours)
• Transmission Type	Per sample (default), Event triggered, Conditional
• Parameter Configuration:	Over-the-air via LoRaWAN® downlinks Locally via wireless connectivity
• Firmware update:	Locally via wireless connectivity, Over The Air

NETWORK CONNECTION AND VISUALISATION

Network Integration

Integratable to all main networks (Actility, Alibaba, Cisco, Digita, Everynet, Kerlink, GeoWAN, kpn, Loriot, machine-Q, Objenious, Orange, Orbiwise, Proximus, Senet, Sens, Swisscom, TATA, The Things Network (TTN), TTI and any other network)

Visualisation and Data Management

Ellenex white label microservice platform and Integratable to all main IIoT platforms directly or through the API(AWS, Azure, PTC ThingWorx, Bosch IoT, Cisco Jasper & Kinetic, Sierra Numerex, MathWorks ThingSpeak, GE Digital Predix, LandisGyr, Siemens MindSphere, Cumulocity, myDevices, Ubidots, TagoIO, AllThingsTalk Maker, HPE IoT and any other major IoT platform).

Ellenex Platform Main Features

- Encrypted ultra-low power communication protocol
- Advanced device inventory
- Integration APIs for enterprise systems
- Multi-tenant role-based access control
- Data export and import
- White-label platform for enterprise runs on private account
- Variable alarm setting for high and low thresholds and multi-channel alerting
- Sampling and transmission interval configuration
- Transmission condition configuration
- Other configurations and customisation available on request



Encrypted & ultra-low power



Integratable



Dynamic alerting



Multi-tenant







Scalable



Composable & API first

MODEL GUIDE

Model	Options:	
<p>C Model (with Hastelloy head):</p> 	 <p>C8: IP68 sealed gauge sensor, compact, POM enclosure with NFC activation</p>	 <p>C5: IP65 vented gauge sensor, compact, POM enclosure with on/off switch</p>
<p>E Model(with Hastelloy head):</p> 	 <p>E5: IP65 sensor (vented gauge), wired, IP65 ASA enclosure and on/off switch</p>	 <p>E7: IP67 sensor (sealed gauge), wired, IP67 ASA enclosure and on/off switch</p>

Note: Ceramic sensor head is similar to the Hastelloy or will be confirmed by the order.

INDUSTRIES



Water & Environment



Agriculture & Farming



Oil & Gas



Marine & Oceanography



Mining & Construction



Smart Building & HVAC



Transport & Logistics



Food & Beverage



Hydraulics and Compressed Air Systems

APPLICATIONS

- Wastewater Pump Performance Monitoring
- Corrosive Liquid Pipeline Pressure Monitoring
- Pressurised System Monitoring
- Corrosive Liquid Storage Level Monitoring
- Spraying System Monitoring
- Compressed Corrosive Gas Monitoring

ORDERING CODE

PTC2-L										
Frequency Zone										
AS (AS923)		EU (EU868)		USx (US902-928, sub-band x)			AUx (AU915-928, sub-band x)		Others	
LoRaWAN® Activation										
A (Over The Air Activation - OTAA)						P (Activation By Personalization ABP)				
Pressure Range										
0.5, 1, 2, 5, 10, 20, 50, 100, 200bar (or any other positive or negative ranges)										
Sensor Head Material										
H: Hastelloy diaphragm and process connection				C: ceramic diaphragm with PVDF process connection				Others		
Pressure Reference										
V (vented gauge)			S (sealed gauge)				A (absolute)			
Process Port										
G1/2 (½" BSPP male)						Others as specified				
Enclosure										
C5		C8		E5		E7		E8		
Compact				Standard cable length: 1m (or other options on request)						
Device Activation										
S: on/off switch						N: NFC (by mobile phone)				
X: No switch (always on)						D: Dual switch (on/off + Trigger)				
Antenna										
I: Internal						E: External				
Options										
(On request)										
PTC2-L	AS	A	0.5bar	H	V	G1/2	C5	S	E	

Sample Product Code:

- **PTC2-L-AS-A-0.5bar-V-G1/2-C5-S-E**

Corrosion resistant pressure sensor operated on LoRaWAN®, frequency of AS923, Over The Air Activated, range of 0.5bar vented, wetted material of Hastelloy, process connection of G1/2, with C5 housing (compact and IP65 rated), activated by on-off switch and external antenna.